

**U.S. DEPARTMENT OF LABOR
Occupational Safety & Health Adm.
MATERIAL SAFETY DATA SHEET**

SECTION I					
MANUFACTURER'S NAME READY SEAL, INC.			EMERGENCY TELEPHONE NO. (800) 424-9300		
ADDRESS, City, State, & Zip Code 1440 S. State Hwy 121, Suite #3, Lewisville, TX 75067					
CHEMICAL NAME & SYNONYMS Ready Seal "OS"			TRADE NAME AND SYNONYMS NA		
CHEMICAL FAMILY Wood Sealer			FORMULA NA		
SECTION II HAZARDOUS INGREDIENTS					
PAINTS, PRESERVATIVES & Solvents	%	TLV (Units)	ALLOYS & METALLIC COATINGS	%	TLV (Units)
PIGMENTS	NA		BASE METAL	NA	
CATALYST	NA		ALLOYS	NA	
VEHICLE	NA		METALLIC COATINGS	NA	
SOLVENTS	X		FILLER METAL PLUS COATING OR CORE FLUX	NA	
ADDITIVES	NA		OTHERS		
OTHERS					
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Distillates, Petroleum, Hydrated Light CAS 64742-47-8				9	NA
Proprietary Wood Preservative				<2	<100 ppm
SECTION III PHYSICAL DATA					
BOILING POINT (Degrees F.)	NA	SPECIFIC GRAVITY (H20=1)		NA	
VAPOR PRESSURE (mm Hg.)	NA	VOLATILE CONTENT PER LITER		<100 gpl	
VAPOR DENSITY (AIR = 1)	NA	EVAPORATION RATE (_____ = 1)		NA	
SOLUBILITY IN WATER	NA				
APPEARANCE & COLOR	Brown liquid;				
SECTION IV FIRE AND EXPLOSION HAZARD DATA					
FLASH POINT (method used) 210° Fahrenheit	FLAMMABLE LIMITS NA		Lei	Uei	
EXTINGUISHING MEDIA NA					
SPECIAL FIRE FIGHTING PROCEDURES Carbon Dioxide, dry chemical, foam or water fog;					
UNUSUAL FIRE & EXPLOSION HAZARDS NA					

SECTION V HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE **NA**EFFECTS OF OVEREXPOSURE **Over exposure of solvent vapors may lead to central nervous system depression. Excessive inhalation of vapors may cause nasal and respiratory irritation.**EMERGENCY & FIRST AID PROCEDURES: **If breathing is difficult have trained person administer oxygen. Flush eyes with water. If irritation exists obtain medical attention. Wash exposed skin areas with soap and water. Do not induce vomiting.**

SECTION VI REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	

INCOMPATIBILITY (Materials to avoid)
NAHAZARDOUS DECOMPOSITION PRODUCTS
NA

HAZARDOUS POLYMERIZATION	MAY OCCUR	NA	CONDITIONS TO AVOID
	WILL NOT OCCUR	NA	

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Absorb into inert material and dispose of according to federal, state, and local regulations.

WASTE DISPOSAL METHOD

Dispose of according to federal, state, and local regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (Specify type) **NIOSH/MSHA Approved Respiratory Protection**

VENTILATION YES	LOCAL EXHAUST	NA	SPECIAL	NA
	MECHANICAL (General)	NA	OTHER	

PROTECTIVE GLOVES **Rubber Gloves** EYE PROTECTION **Goggles and Face Shield**OTHER PROTECTIVE EQUIPMENT **Rubber suit and shoes;**

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING **Store away from heat, sparks, and open flames. Protect container from physical damage.**OTHER PRECAUTIONS: **Excessive inhalation of solvent vapors may cause headache, dizziness or nausea. Repeated or prolonged exposure to solvent vapors may cause liver damage. Ingestion may cause gastrointestinal irritation. If ingested, do not induce vomiting. Seek medical attention.**